## Hard Faced Single Cartridge Seal

- ➤ ASP Stainless Steel Single Cartridge Seal
- Balanced


Multi-Directional

➤ SC / SC Hard Face Standard

ASP SCS single cartridge seals are fully preassembled. They are balanced and can be used in either direction of rotation. The energizing springs hold the seal faces together from outside the stuffing box, keeping them from clogging and losing compression. By making all of our seal faces "hard faces" your seals will last. In the short run our ASP SCS will help reduce your mechanical seal cost. In the long run your maintenance and clean up expenses are reduced. Our seals protect your bearings, and your budget.

Flush Connection included





SEAL	d3									G
(Inches)	d2	min.	max.	d4	L1	L3	L4	d5	S	(Inches)
1	1.69	1.73	2.01	4.13	2.64	0.969	1	2.44	0.551	1/4
1.125	1.81	1.85	2.05	4.13	2.64	0.969	1	2.44	0.551	1/4
1.18	1.89	1.93	2.2	4.13	2.64	0.969	1	2.56	0.551	1/4
1.375	1.97	2.01	2.24	4.33	2.64	0.969	1	2.64	0.551	1/4
1.38	2.09	2.13	2.4	4.45	2.64	0.969	1	2.76	0.551	1/4
1.5	2.2	2.24	2.6	4.84	2.64	0.969	1	2.95	0.551	3/8
1.57	2.28	2.32	2.68	4.84	2.64	0.969	1	2.95	0.63	3/8
1.63	2.36	2.42	2.78	5.24	2.64	0.969	1	3.15	0.63	3/8
1.75	2.46	2.52	2.87	5.43	2.64	0.969	1	3.19	0.63	3/8
1.875	2.58	2.64	2.95	5.43	2.64	0.969	1	3.31	0.63	3/8
2	2.68	2.72	3.07	5.83	2.64	0.969	1	3.43	0.63	3/8
2.125	2.87	2.91	3.27	5.83	2.64	0.969	1	3.54	0.709	3/8
2.375	3.07	3.11	3.58	6.18	2.64	0.969	1	4.02	0.709	3/8
2.5	3.27	3.33	3.88	6.42	2.64	0.969	1	4.29	0.709	3/8
2.75	3.66	3.74	4.25	7.01	2.64	0.969	1	4.65	0.709	3/8
3	3.94	4	4.65	7.48	3.31	1.05	1.1	5.08	0.709	3/8
3.125	4.19	4.25	4.88	7.68	3.31	1.05	1.1	5.31	0.709	3/8
3.375	4.31	4.37	5.04	7.8	3.31	1.05	1.1	5.47	0.866	3/8
3.5	4.56	4.63	5.31	8.07	3.31	1.05	1.1	5.71	0.866	3/8
3.75	4.69	4.75	5.43	8.19	3.31	1.05	1.1	5.83	0.866	3/8
4	4.94	5	5.67	8.58	3.31	1.05	1.1	6.06	0.866	3/8

Equal to: Burgmann Cartex-SN, John Crane 88S, Anchor 13SA